

# REX

www.rexind.co.jp

## PIPE THREADING MACHINE


# NP80A series

***A machine that gives you the best finish you've ever seen!***



NP80A

CE  
CE Model  
NP80AV



Threading

- USER FRIENDLY and EASY MAINTENANCE.
- Easy to use, high, productivity, excellent portability.

### Specifications

Model	NP80A/AV/AV III
Threading Capacity	½ B - 3 B (15A - 80A)
Voltage (50/60Hz) AC (V)	110 - 120 or 220 - 230
Motor	Single phase series motor Input 1600W / Output 700W
Rotation Speed (min <sup>-1</sup> )	29 (unloaded)
Weight without DH (kg)	67
Dimensions L x W x H (mm)	690 x 490 x 423



Manual die head  
(for ½"-2" pipe)  
NP80A



Manual die head  
(for 2½"-3" pipe)  
NP80A/AV



NV-auto die head  
(for ½"-2" pipe)  
NP80AV/AV III



Uni-auto V die head  
(for ½"-2" pipe)  
NP80AV/AV III



Self-opening die head  
(for 2½"-3" pipe)  
NP80AV III

- Thread length can be adjusted by just changing the lever contact.
- Makes a smooth, beautifully finished tapered thread with ease.
- The die head is fitted with a micro fine-adjustment dial to simplify fine-adjustment of the thread for each size of pipe. (Self-opening die head)

ISO9001/ISO14001



· Be sure to read the Operation Manual before use.  
· Changes in specifications, colour, etc. may be made without prior notification.

## REX INDUSTRIES CO.,LTD.

Overseas Sales Dept. & Factory :

1-9-3, Hishiya-Higashi, Higashi-Osaka 578-0948, Japan  
Tel.: +81-(0)72-961-9820 Fax.: +81-(0)72-961-9878

1102-E2