

REX

REX COPPER TUBE TOOLS

**CORDLESS
FLARE**

RF20SII

New Release
with Improved Performance
and Ease of Handling!



*Backed up by over 30 years of
expertise in Copper Tube Flaring*



Three Improved Features!


1. More Compact and Lighter in Weight!



23mm shorter
85g lighter than previous model (with battery inserted)

2. Shorter Machining time!

Improved power transmission efficiency shortens machining time and improves accuracy!



3. Increased Productivity!

Increased number of processing times per charge



Rapid charging (around 1 hour)

Specifications

Model		CORDLESS FLARE RF20SII				
Code No.		424941				
Applicable Tube		Copper Tubes (O - Type, OL - Type) JIS H3300				
Applicable Tube Size	Nominal diameter	1/4"	3/8"	1/2"	5/8"	3/4"
	Outer diameter (mm)	6.35	9.52	12.70	15.88	19.05
Rotation Speed		290 min ⁻¹				
Number of processable times		Approx. 250 times : 1/2" copper tubing on a full charge (depending on usage conditions).				
Processing times		Approx. 5 (1/4") - 7 (3/4") seconds				
Dimensions (mm)		W108 x D72 x H261 (with battery inserted)				
Weight (g)		1320 (with battery inserted)				
Standard Accessories		10.8V Li-ion Battery, Charger, Power Cord, Clamp with Liner (x 3), Hex key (2.5mm), Carrying Case				


*Specifications, colour, etc. may change without prior notification.

Lithium-ion Battery

Model		RF20SB
Code No.		424987
Output Voltage		DC10.8V
Capacity		2000mAh
Charging Time**		Approx. 70 min (Approx. 80% charge completed in Approx. 55 minutes)
Charges /Discharges**		Approx 500 times
Chargeable Temperature Range		10 - 40 °C
Dimensions (mm)		W60 x D54 x H85
Weight (g)		185

**depending on usage

Optional Accessories



Hook



Clamp with Flaring Bar (1/4" , 3/8" , 1/2")



REX INDUSTRIES CO., LTD.

Overseas Sales Dept. & Factory :

1-9-3, Hishiyahigashi, Higashi Osaka 578-0948, Japan
Tel.: +81 - (0)72 - 961 - 9820 Fax.: +81 - (0)72 - 961 - 9878

URL <https://www.rexind.co.jp>