



FLARE

cordless RF20SII

with Improved Performance and Ease of Handling! New Release



Backed up by over 30 years of expertise in Copper Tube Flaring







Three Improved Features!

1. More Compact and Lighter in Weight!



85g lighter than previous model (with battery inserted)

2. Shorter Machining time!

Improved power transmission efficiency shortens machining time and improves accuracy!



3. Increased **Productivity!**

Increased number of processing times per charge



Rapid charging (around 1 hour)

Specifications

Model	CORDLESS FLARE RF20SII				
Code No.	424941				
Applicable Tube	Copper Tubes (O - Type, OL - Type) JIS H3300				
Applicable Nominal diameter	1/4"	3/8"	1/2"	5/8"	3/4"
Tube Size Outer diameter (mm)	6.35	9.52	12.70	15.88	19.05
Rotation Speed	290 min-1				
Number of processable times	Approx. 250 times : 1/2" copper tubing on a full charge (depending on usage conditions).				
Processing times	Approx. 5 (1/4") - 7 (3/4") seconds				
Dimensions (mm)	W108 x D72 x H261 (with battery inserted)				
Weight (g)	1320 (with battery inserted)				
Standard Accessories	10.8V Li-ion Battery, Charger, Power Cord, Clamp with Liner (x 3), Hex key (2.5mm), Carrying Case				

^{*}Specifications, colour, etc. may change without prior notification.

Lithium-ion Battery

Model	RF20SB		
Code No.	424987		
Output Voltage	DC10.8V		
Capacity	2000mAh		
	Approx. 70 min		
Charging Time**	(Approx. 80% charge completed in Approx. 55 minutes)		
Charges /Discharges**	Approx 500 times		
Chargeable Temperature Range	10 - 40 ℃		
Dimensions (mm)	W60 x D54 x H85		
Weight (g)	185		

^{**}depending on usage

Optional Accessories





REX INDUSTRIES CO., LTD.

Overseas Sales Dept. & Factory:

1-9-3, Hishiyahigashi, Higashi Osaka 578-0948, Japan Tel.: +81 - (0)72 - 961 - 9820 Fax.: +81 - (0)72 - 961 - 9878

URL https://www.rexind.co.jp