REX
www.rexind.co.jp

PIPE THREADING MACHINE

NP80A series

A machine that gives you the best finish you've ever seen!

Manual die head
(for ½"-2" pipe)
NP80A

Manual die head
(for 2½"-3" pipe)
NP80A/AV

- USER FRIENDLY and EASY MAINTENANCE.
- Easy to use, high, productivity, excellent portability.

NV-auto die head
(for ½"-2" pipe)
NP80AV/AVⅢ

Uni-auto V die head
(for ½"-2" pipe)
NP80AV/AVⅢ

Self-opening die head
(for 2½"-3" pipe)
NP80AVⅢ

Specifications

Model	NP80AV/AV/AVⅢ
Threading Capacity	½B - 3B (15A - 80A)
Voltage (50/60Hz) AC (V)	110 - 120 or 220 - 230
Motor	Single phase series motor Imput 1600W / Output 700W
Rotation Speed (min^{-1})	29 (unloaded)
Weight without DH (kg)	67
Dimensions L x W x H (mm)	690 x 490 x 423

- Thread length can be adjusted by just changing the lever contact.
- Makes a smooth, beautifully finished tapered thread with ease.
- The die head is fitted with a micro fine-adjustment dial to simplifly fine-adjustment of the thread for each size of pipe. (Self-opening die head)

ISO9001 ; 2000 : JQA-2387 / ISO14001 : JQA-EM2926

REX INDUSTRIES CO.,LTD.

Overseas Sales Dept. & Factory :
1-9-3, Hishiya-Higashi, Higashi-Osaka 578-0948, Japan
Tel.: +81-(0)72-961-9820 Fax.: +81-(0)72-961-9878

· Be sure to read the Operation Manual before use.
· Changes in specifications, colour, etc. may be made without prior notification.

1102-E1