





Optional Equipment Chart

* See the Compatibility tables.*** discontinued** Die head holder required.															
	Capacity (in.)	Voltage	Weight (kg) w/o DH	Manual Die Head*	Uni-auto* Die Head	NV-auto* Die Head	Self-opening* Die Head	Profiling* Die Head	Roll Thread Head For sale in Japan only	Grooving / Beveling* Die Head	Portable Groover	Threader cart / Caster	CE Foot Switch Version		
F25A 	1/4 - 1	110 V, 120 V 220/230 V	19.8	1/4"-1" BSPT NPT 3/8"-3/4" BSW  MD25A	—	—	1/4"-3/8" 1/2"-1" BSPT NPT  SOD10A/25A	—	—	—	—	—	—		
S40A 	1/4 - 1½	110 V, 120 V	32	1/4"-3/8" BSPT NPT 5/16"-7/8" BSW  MD10A 1/2"-1½" BSPT NPT Metric UNC PF C  MD40A	 UAD40A 1/2"-1½" BSPT NPT	—	1/2"-3/4" BSPT NPT  SOD20A 1"-1½" BSPT  SOD40A	—	3/8" 1/2" 3/4" BSPT  SRH-10A SRH-15A SRH-20A	—	—	—			
FP50A 	1/4 - 2	110 V, 120 V 220/230 V	48	 MD10A 1/2"-2" BSPT NPT BSW Metric UNC NPSM BSPP PF C  MD50A	 UAD50A 1/2"-2" BSPT NPT	 NVAD50A 1/2"-2" BSPT NPT	 SOD10A/25A** +Die head holder  SOD20A/40A 1"-2" BSPT NPT  SOD50A	—	3/8" 1/2" 3/4" 1" BSPT  SRH-10A SRH-15A SRH-20A SRH-25A	 GV/BVD50A	 RG-R0 with respective mount base M-R series	 Threader Cart*** with respective adapter	 Available		
FR50A 	1/4 - 2	110 V, 120 V 220/230 V	48	1/4"-2" BSPT NPT  MD50A-R	 UAD50A-R*** 1/2"-2" BSPT NPT	 NVAD50A-R 1/2"-2" BSPT NPT	—	—	—	—					
NP80A 	1/4 - 3	110 V 220/230 V	67	 MD10A 2½"-3" BSPT NPT BSPP PF C  MD40A  MD50A  MD80A	 UAD50A 1/2"-2" BSPT NPT	 NVAD50A 1/2"-2" BSPT NPT	 SOD10A/25A** +Die head holder  SOD20A/40A  SOD50A  SOD80A	2½"-3" BSPT (Self- Profiling)  SPD80A	3/8" 1/2" 3/4" 1" 1¼" 1½" 2" BSPT  SRH-10A SRH-15A SRH-20A SRH-25A SRH-32A SRH-40A SRH-50A	 GV/BVD50A ¾"- 2"  GV/BVD80A 2½"- 3"	 RG-RH with respective mounting kit M-HR series	 Caster	 Available		
N100A 	1/4 - 4	110 V,120 V 220/230 V	123	 MD10A 3½"-4" PF  MD50A  MD40A  MD80A  MD100A***			 UAD50A 1/2"-2" BSPT NPT	 NVAD50A 1/2"-2" BSPT NPT	 SOD20A/40A  SOD50A  SOD80A	 SPD80A 2½"-4" BSPT NPT  PD100A				 SRH-10A SRH-15A SRH-20A SRH-25A SRH-32A SRH-40A SRH-50A	 GV/BVD50A ¾"- 2"  GV/BVD80A 2½"- 3" GV/BVD80A
150A 	2½ - 6	110 V,120 V 220/230 V	170	—	—	—	—	2½"-4" BSPT NPT  PD100A-6" 5"-6" BSPT NPT  PD150A	—	 GV/BVD100A 2½"- 4"  GV/BVD150A 5"- 6"	—	—	 Caster	—	
Example of setting															
Cutaway view				BSPT NPT  Tapered Pipe	BSPP PF C NPSM  Straight Pipe	Metric BSW UNC  Straight Bolt				 Roll Thread	 Cut Grooving	 Beveling	 Roll Grooving		
Features				· Die head and dies for steel pipes and bars.				· Eco-friendly · Reduces costs · Damage-resistant · Rust-resistant · Leak-resistant			Grooving dies for making grooves in internally lined steel pipes and thick-walled pipes. Beveling dies for reaming welded pipes.		Plasticity processing increases strength. For coupling joints.		